RTiPanel App

Fully customizable using RTI's Integration Designer® programming software, the RTiPanel offers the same intuitive control experience RTI remote controls offer. Compatible with Apple iOS, Android and Microsoft Windows PCs, the RTiPanel App provides local or remote access to an RTI control system via LAN or Wi-Fi and off site control via WAN or cellular data. In addition to full control of the AV electronics, users can view and adjust thermostats, security systems and lights, from home, the office, on vacation, or virtually anywhere in between.*

For licensing options and installation information, please visit the dealer section of www.rticorp.com.

Key Features

- Control and receive feedback from audio, video, lighting, security, climate, and more!
- RTiPanel app available through Apple App Store®, Google Play® and the Amazon App Store®
- Fully integrate Apple iPad®, iPhone®, iPod Touch®, Android™ devices and Windows® PCs into RTI control systems utilizing an XP series and RP-4 control processor.
- Completely customizable graphical interface.
- Supports creation of both portrait and landscape views with minimal extra programming required.
- RTiPanel supports full two-way feedback, including cover art, graphics, text, dynamic scrolling lists, and more (* Requires XP processor).
- Supports local connection via LAN, and off-site access via WiFi® or cellular data (if available), with automatic switching.
- Highly optimized for fast connection times.
- Control system programming stored on Apple/Android/Windows devices and updates automatically when changes are made.

Compatible with MS Windows, iOS, Android devices and SURFiR

* Smart devices and SURFiR® sold separately

www.rticorp.com

It's Under Control®

System Requirements

General
- RTI XP series control processor (two-way control) or RP4 control processor (one-way control).
- The device running the RTiPanel App and the control processor must be connected to the Ethernet network.
- Remote access requires a connection to the Internet and either a static IP address from the ISP (Internet Service Provider), or a dynamic DNS account implemented.
- Two-way control and off-site access requires an XP series control processor.

Apple iOS Devices
- RTiPanel App compatible with Apple iPad and iPhone.
- Apple devices require iOS 3.2 or higher (* Subject to change without notice.)

Android Devices
- Requires an XP series control processor (not compatible with RP-4).
- RTiPanel App compatible with Android smart phone and tablet devices.
- Android devices with touchscreen displays larger than 5.5" will require a tablet license.
- Android devices require 2.1 or higher (*Subject to change without notice.)

Microsoft Windows PCs
- IBM or compatible personal computer running Microsoft Windows XP, Windows Vista, Windows 7, Windows 8 or higher operating system.
- At least 256 Megabytes (MB) of RAM.
- 16 bit color monitor (16 bit color 1024x768 or better recommended, 256 colors not supported).
- PC and XP series control processor must be connected to the Ethernet network.

Android is a trademark of Google Inc.

Apple iPad, iPhone, iPod Touch and Apple App Store are registered trademarks of Apple Inc.

NOTES:
- The RTiPanel App can be downloaded for free, however, licensing and programming fees will apply. Please contact an RTI dealer for further information.
- Features and system requirements subject to change without notice.

RTI User Interfaces

Remote Controls	In-Wall Touchpanels
Keypads	Tabletop Touchpanels
Audio Control Keypads	Mobile Apps

RTI Control Accessories

Control Processors	IR Modules
System Kits	Relay Modules
RS-232 Modules	Z-Wave Modules

RTI Audio/Video Distribution

HDMI Splitters & Switchers	HDBaseT Extenders
HDMI Matrix Switchers	Presentation Switchers
HDBaseT Matrix Switchers	Video over IP Transceivers

It's Under Control®

1811